

FANLESS &VENTLESS DESIGN



Equipped a PCAP touch

to create a precise and

An aluminum die-casting back cover is designed to be fanless and ventless to provide well heat dissipation.



HIGH LEVEL OF INGRESS PROTECTION

The sealed, IP65-rated front bezel makes it easy for cleanup as well as protect the system against water, dust, grease and food build-up.

RUGGED& RELIABLE

Well-engineered, high performance and reliable technology combiend with modern and innovative design.





SPECIFICATIONS

15" LED-backlight

Bezel-free Projected Capacitive Touch

Configuration Intel Celeron J1900 up to 2.4GHz

(Quad-core)

DDR3L RAM*1 slot, Max. 8GB

2.5" SATA HDD/SSD

External power supply AC100-240V full range

Operating System

Windows 7/POSReady 7/

Windos 10 IoT Enterprise/

Linux Kernel 3.0 or above

I/O 3 x USB2.0

Connectivity 1 x USB3.0

1 x eSATAp/USB2.0 combo

4 x COM

1 x Gigabit LAN

1 x Line out

1 x VGA

1 x Cash drawer

1 x DC 12V out

1 x DC 24V in

Options 2nd hard drive/SSD

10" 2nd LCD Display (IPS)

VFD Customer Display

Magnetic Stripe Reader

iButton Detector

Biometrics Fingerprint Recognizer

RFID Reader

2-in-1 Identification Reader

(MSR/Fingerprint/iButton/RFID/NFC)



